



## GLOSS KILLER 44/00006

A POWDER MATTE AGENT FOR POST-ADDITION TO SMOOTH FLOW POWDER COATINGS

### Typical applications

- use for interior applications for all TIGER powder series without limitation
- for exterior application use only in conjunction with series 59, 47 and 44

DO NOT use for architectural applications

<b>Standard Packaging</b>	in 20 kg cartons Minipack 2,5 kg
<b>Storage Stability</b>	6 months at no more than 25°C, avoid direct and extended heat exposure!

### Features

- achieves continuous matting from 30 - 60 gloss\*

\*Gloss level acc. to ISO 2813/60° angle

### Finish

- semi-matte:  
add 10 % to 20 % to the powder coating
- matte:  
add 20 % to 30 % to the powder coating

### Concentration

Mix only 10 % to 50 % of the Gloss Killer agent to the powder coating. Any mix in excess of 30 % to 50 % may result in a weakened hiding power.

Prior to further processing it is required that the buyer and/or user verifies the optimum mixing ratio and the suitability of processes or applications.



## Use

The Gloss Killer is dry blended to the powder coating. While mixing of bigger quantities may be done using drum or roll mixers, smaller quantities may be mixed manually.

Please note, that this is polyurethane-based product adhering to the relevant cure agenda is imperative (for more information please see product data sheet 1154).

Our verbal and written recommendations for the use of our products are based upon experience and in accordance with present technological standards. These are given in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of our products for the intended application. We warrant that our products are free of flaws and defects to the extent as stipulated in our Terms of Delivery and Payment.

As a part of our product information program each of our Product Data Sheets are periodically updated, so that the latest version shall prevail. Therefore, please visit the download area of [www.tiger-coatings.com](http://www.tiger-coatings.com) to make sure you have the most current version of this Product Data Sheet. The information in our Product Data Sheets is subject to change without notification.

**This Product Data Sheet substitutes any and all previous Product Data Sheets and notes for customers published on this subject matter and is only intended to give a general product overview. Please request specific information for products outside of our standard product list (latest version).**

The Technical Information Sheets and the Terms of Delivery and Payment each in their latest version, available as a download at [www.tiger-coatings.com](http://www.tiger-coatings.com), form an integral part of this Product Data Sheet.

certified according to  
EN ISO 9001 / 14001



### TIGER Coatings GmbH & Co. KG

Negrellistrasse 36

4600 Wels | Austria

T +43 / (0)7242 / 400-0

F +43 / (0)7242 / 650 08

E [powdercoatings@tiger-coatings.com](mailto:powdercoatings@tiger-coatings.com)

W [www.tiger-coatings.com](http://www.tiger-coatings.com)